

DATA SHEET

Detachable Battery Pack *BTR-09*



BTR-09

The Detachable Battery Pack, BTR-08 is used exclusively for Fujikura Fusion Splicer, 70 and 19 Series.

The rechargeable battery is charged by connecting to ADC-18 AC adaptor using DCC-18 charge cord.

SPECIFICATIONS	
Model	BTR-09
Type	Lithium battery
Output voltage	14.8V
Battery capacity	4.0Ah
Battery charger	Exclusive Battery charger, ADC-18 Battery charge cord, DCC-18
Expected battery cycle life	Max. 500 cycles
Battery capacity indicator	Available
Operating condition	-10 to +50 degree C / Non dew
Dimension, Weight	132W x 117D x 38H (mm), 558g
Use for	70 Series, 19 Series

USAGE CONDITION
Due to the nature of Li-ion battery, store in a cool place and half charged (not fully charged, not fully discharged) reduces the aging effect.

PERFORMANCE		
No. of splicer operation (Splicing / tube heating)	Splicer model	BTR-08
	70S/80S	200 cycles
	19S	200 cycles



**DCC-18
Charge cord**

Specifications and descriptions are subjected to change without prior notice.

Fujikura Ltd.	1-5-1, Kiba, Koto-ku, Tokyo 135-8512, Japan Phone : +81-3-5606-1164 Fax : +81-3-5606-1534 http://www.fujikura.co.jp
Fujikura Asia Ltd.	438A Alexandra Road, Block A Alexandra Technopark #08-03 Singapore 119967 Phone : +65-6-278-8955 Fax : +65-6-278-0965 http://www.fujikura.com.sg
Fujikura Europe Ltd.	C51 Barwell Buisiness Park, Leatherhead Road, Chessington, Surrey KT9 2NY, UK Phone : +44-20-8240-2000 Fax : +44-20-8240-2010 http://www.fujikura.co.uk
AFL Telecommunications	260, Parkway East, Duncan, SC29334, USA Phone : +1-800-235-3423 Fax : +1-800-926-0007 http://www.afglobal.com
Fujikura (China) Co., Ltd.	16 th Floor, Shanghai Hang Seng Bank Tower, 1000 Lujiazui Ring Road, Pudong New Area, Shanghai 200120, CHINA Phone : +86-21-6841-3636 Fax : +86-21-6841-2070 http://www.fujikura.com.cn